

■パイプ：取扱表

角パイプ

正方形	長方形
1.2×13×13	1.2×19×10
1.6×16×16	1.2×22×10
1.6×19×19	1.2×25×12
1.6×25×25	1.6×30×20
1.6×31×31	1.6×32×14
1.6×32×32	1.6×40×20
1.6×40×40	1.6×40×25
1.6×45×45	1.6×50×26
2.0×40×40	1.6×60×30
1.6×50×50	2.3×60×30
2.3×50×50	2.3×75×45
3.2×50×50	3.2×75×45
2.3×60×60	2.3×100×50
3.2×60×60	3.2×100×50
2.3×75×75	3.2×125×75
3.2×75×75	3.2×150×75
2.3×80×80	3.2×150×100
3.2×80×80	4.5×150×100
2.3×100×100	6.0×150×100
3.2×100×100	4.5×200×100
4.5×100×100	6.0×200×100
6.0×100×100	
3.2×125×125	
4.5×125×125	
6.0×125×125	
4.5×150×150	

一般構造用鋼管 (STK)

寸法
21.7×1.9
27.2×1.9
27.2×2.3
34.0×2.3
42.7×2.3
48.6×2.3
60.5×2.3
76.3×2.8
89.1×2.8
101.6×3.2
114.3×3.5
139.8×3.5
165.2×3.7
216.3×4.5

コラム

寸法
6×200×200
8×200×200
9×200×200
12×200×200
6×250×250
9×250×250
12×250×250
16×250×250
6×300×300
9×300×300
12×300×300
16×300×300
19×300×300
9×350×350
12×350×350
16×350×350
19×350×350
9×400×400
12×400×400
16×400×400
19×400×400

配管用鋼管 (SGP/STPG)

呼称	外径	肉厚			
		SGP	STPG		
			Sch40	Sch60	Sch80
6A	10.5	2.0	1.7	2.2	2.4
8A	13.8	2.3	2.2	2.4	3.0
10A	17.3	2.3	2.3	2.8	3.2
15A	21.7	2.8	2.8	3.2	3.7
20A	27.2	2.8	2.9	3.4	3.9
25A	34.0	3.2	3.4	3.9	4.5
32A	42.7	3.5	3.6	4.5	4.9
40A	48.6	3.5	3.7	4.5	5.1
50A	60.5	3.8	3.9	4.9	5.5
65A	76.3	4.2	5.2	6.0	7.0
80A	89.1	4.2	5.5	6.6	7.6
90A	101.6	4.2	5.7	7.0	8.1
100A	114.3	4.5	6.0	7.1	8.6
125A	139.8	4.5	6.6	8.1	9.5
150A	165.2	5.0	7.1	9.3	11.0
175A	190.7	5.3			
200A	216.3	5.8	8.2	10.3	12.7
225A	241.8	6.2			
250A	267.4	6.6	9.3	12.7	15.1
300A	318.5	6.9	10.3	14.3	17.4
350A	355.6	7.9	11.1	15.1	19.0
400A	406.4	7.9	12.7	16.7	21.4