

■鋼板：取扱表

熱間圧延鋼板

厚さ	3×6	4×8	5×10
0.8	✓	✓	
1	✓	✓	
1.2	✓	✓	
1.6	✓	✓	✓
2.3	✓	✓	✓
3.2	✓	✓	✓
4.5	✓	✓	✓
6	✓	✓	✓
8	✓	✓	✓
9	✓	✓	✓
10	✓	✓	✓
12	✓	✓	✓
16	✓	✓	✓
19	✓	✓	✓
22	✓	✓	✓
25	✓	✓	✓
28	✓	✓	✓
30	✓	✓	✓
32	✓	✓	✓
36	✓	✓	✓
38	✓	✓	✓
40	✓	✓	✓
45	✓	✓	✓
50	✓	✓	✓

酸洗鋼板

厚さ	3×6	4×8	5×10
1.6	✓	✓	✓
2.3	✓	✓	✓
3.2	✓	✓	✓
4.5	✓	✓	✓
6	✓	✓	✓

SPCC

厚さ	3×6	4×8
0.6	✓	✓
0.8	✓	✓
1	✓	✓
1.2	✓	✓
1.6	✓	✓
2.3	✓	✓
3.2	✓	✓

亜鉛

厚さ	3×6	4×8
1	✓	✓
1.2	✓	✓
1.6	✓	✓
2.3	✓	✓
3.2	✓	✓
4.5	✓	✓

縞鋼板（メーカー：中山・神戸）

厚さ	914×1829	1219×2438	1524×3048
3.2	✓	✓	✓
4.5	✓	✓	✓
6.0	✓	✓	✓
9.0	✓	✓	✓
12.0	✓	✓	✓

エキスパンドメタル（ソロバン目・タタミ目）

記号	厚さ	目の大きさ	3×6	4×8
XS-31	1.2	12×30.5	✓	✓
XS-32	1.6	12×30.5	✓	✓
XS-33	2.3	12×30.5	✓	✓
XS-41	1.6	22×50.8	✓	✓
XS-42	2.3	22×50.8	✓	✓
XS-43	3.2	22×50.8	✓	✓
XS-61	2.3	34×76.2	✓	✓
XS-62	3.2	34×76.2	✓	✓
XS-63	4.5	34×76.2	✓	✓
XG-21	4.5	36×101.6	✓	✓
XG-22	6.0	36×101.6	✓	✓
XG-24	8.0	36×101.6	✓	✓